



JP ENTERPRISES

JPABP ADJUSTABLE BUTT PLATE FOR MAGPUL PRS STOCK

www.jp Rifles.com

CAUTION: REMOVE THE MAGAZINE AND VISUALLY CHECK THE CHAMBER TO ENSURE THAT YOUR FIREARM IS UNLOADED.

Parts Included:

- Butt pad adapter
- Adjustment plate
- One (1) 10-24 x 1/2" flat head cap screw
- One (1) 10-24 x 3/4" flat head cap screw
- Three (3) 10-32 x 1/2" button socket cap screw

The JPABP is a drop-in component for the Magpul PRS stock adding versatility without any troublesome modification of parts. The JPABP allows for 2.5" upward adjustment and 2" downward adjustment of the standard PRS butt pad as well as 10° left and right cant adjustment.



INSTALLATION INSTRUCTIONS

1. Using a 1/8" hex key, unscrew and remove the two 10-32 button socket cap screws securing the rubber butt pad of the Magpul PRS stock. Remove the rubber butt pad and set it aside with the screws.
2. Attach the JPABP butt pad adapter piece to the stock using the two 10-24 flat head cap screws provided. Make sure to install the shorter (1/2") screw in the top hole and the longer (3/4") screw in the bottom hole. For a secure, permanent installation, you can apply a small amount of thread locker to these screws before installing them. If so, allow the thread locker an appropriate time to set according to the individual product's instructions.

Visit us at www.jp Rifles.com

Rev. 11.12

P.O. Box 378, HUGO, MN 55038 | VOICE: 651-426-9196 | FAX: 651-426-2472

- Using the various threaded holes in the butt pad adapter, install the three provided button socket cap screws to attach the adjustment plate as desired.

While the adjustment plate can be attached using only two screws, we strongly recommend securing the plate at three points using all three screws.

Once the plate orientation is to your liking, tighten the button socket cap screws securely to prevent movement of the adjustment plate. You can again choose to apply thread locker to these screws, but it will make any further adjustments cumbersome.



- Reattach the original rubber butt plate of the PRS to the Adjustment plate using the stock's original 10-32 button socket cap screws.

THANKS FOR YOUR BUSINESS!