



J P E N T E R P R I S E S

---

## AR-15 CLEANING ROD GUIDE

AVOID ACCURACY LOSS DUE TO DAMAGED CROWN, THROAT OR CHAMBER

**JPRG-1 Red**

---

**Remove magazine and visually check chamber before performing any work.**

The JP Cleaning Rod Guide has two O-ring grooves for adjustable retention, the second groove position giving .005 larger OD on the ring for more retention in the receiver. To use the cleaning rod guide, lubricate the O-rings before use. Remove bolt assembly and insert JP rod guide in upper receiver with a twisting motion. Align the solvent hole at the ejection port and perform normal cleaning procedures through the guide. When satisfied with the bore, remove guide and clean chamber with AR chamber/locking lug brush and mop. For calibers exceeding .257 bore, use of a smaller cleaning jag may be required.

---

*Visit us on the web at [www.jp Rifles.com](http://www.jp Rifles.com).*



J P E N T E R P R I S E S

---

## AR-10/SR-25 .308 CLEANING ROD GUIDE

AVOID ACCURACY LOSS DUE TO DAMAGED CROWN, THROAT OR CHAMBER

**JPRG-2 Blue**

---

**Remove magazine and visually check chamber to make certain that weapon is clear before performing any work.**

To use the JP Cleaning Rod Guide, lubricate the O-rings before use. Remove bolt assembly and insert JP rod guide in upper receiver with a twisting motion. Align the solvent hole at the ejection port and perform normal cleaning procedures through the guide. When satisfied with the bore, remove guide and clean chamber with AR chamber/locking lug brush and mop. For calibers exceeding .312 bore, use of a smaller cleaning jag may be required.

---

*Visit us on the web at [www.jp Rifles.com](http://www.jp Rifles.com).*